



Saas Instruments
Henry Fordin katu 5 B
FI-00150 HELSINKI
Tel. +358 9 6860 610
Fax +358 9 6860 6130
www.saas.fi

Highline sauna glass fiber

Installing the projector

The projector is mounted under the benches to a maximum height of one metre above the floor.

1. Attach the projector to the wall with two screws. There are places for the screws on the sides of the projector.
2. The projector is to be securely connected to the the electricity grid. Connections should be made only by a competent electrician.
3. The common end of the fibre bundle is installed to the projector by pressing while turning the end into the hole in the projector.

Installing the fibres

Select the locations of your desired light spots. Check the adequacy of fibres for the desired locations and determine the location of the points.

Drill holes of 3.5 mm for the fibres, insert the fibre through the hole and, if necessary, ensure the retention of the fibre with (epoxy) adhesive. The installation hole of the sleeve of the stove lens is 15 mm.

Fiber optic cables do not require separate tubing, but they can rather be drawn among insulation wool. Ensure that the fiber optic cable is not pinched or bent into too sharp of a turn ($r = 15$ mm). Handle the fiber optic cable with care! If the fiber optic cable is damaged, the light conductivity decreases. Attach the fiber optic cables and make the necessary grooves into the floor joists, so that the paneling is successful.

